SUPERELEVATION TABLE			
Design Speed	Maximum e*	Minimum Radius ft.	Max. Deg. of Curve
30	0.04	302	19 00'
40	0.04	573	10 00'
50	0.04	955	6 00'
60	0.04	1,528	3 45'
30	0.06	273	21 00'
40	0.06	509	11 15'
50	0.06	849	6 45
60	0.06	1,380	4 15'
30	0.08	252	22 45'
40	0.08	468	12 15'
50	0.08	764	7 30'
60	0.08	1,206	4 45'

e* = rate of roadway superelevation, foot per foot

D. Intersections

1. Streets shall be laid out so as to intersect as nearly as possible at right angles, and no street should intersect any other street at an angle less than sixty-five (65) degrees. No street should intersect a railroad at grade at an angle less than sixty-five (65) degrees.

2. Property lines at intersections should be set so that the distance from the edge of pavement, of the street turnout, to the property line will be at least as great as the distance from the edge of pavement to the property line along the intersecting streets. This property line can be established as a radius or as a sight triangle. Greater offsets from the edge of pavement to the property lines will be required, if necessary, to provide sight distance for the stopped vehicle on the side street.

3. Offset intersections are to be avoided. Intersections which cannot be aligned should be separated by a minimum length of 200 feet between survey centerlines.

E. Cul-de-sacs

Cul-de-sacs shall not be more than seven hundred (700) feet in length. The distance from the edge of pavement on the vehicular turn-around to the right-of-way line should not be less than the distance from the edge of pavement to right-of-way line on the street approaching the turn-around. Cul-de-